

3 bar								
Model		300	500	800	1000	1500	2000	2500
Inhoud	L	300	500	800	1000	1500	2000	2500
Hoogte H / Montagehoogte Hm	mm	1410/1432	1700/1727	1840/1878	2039/2075	2170/2222	2132/2202	2363/2432
Diameter D	mm	ø 550	ø 650	ø 790	ø 790	ø 1000	ø 1200	ø 1250
Bedrijfsdruk	bar	3	3	3	3	3	3	3
Gewicht (zonder isolatie)	kg	56	75	102	120	201	251	292
Model		3000	4000	5000	6000	7000	8000	9000
Inhoud	L	3000	4000	5000	6000	7000	8000	9000
Hoogte H / Montagehoogte Hm	mm	2715/2775	2745/2815	2870/2960	3370/3447	3101/3185	3545/3620	3290/3405
Diameter D	mm	ø 1250	ø 1400	ø 1600	ø 1600	ø 1800	ø 1800	ø 2000
Bedrijfsdruk	bar	3	3	3	3	3	3	3
Gewicht (zonder isolatie)	kg	330	470	574	652	750	830	900
6 bar								
Model		300	500	800	1000	1500	2000	2500
Inhoud	L	300	500	800	1000	1500	2000	2500
Hoogte H / Montagehoogte Hm	mm	1410/1432	1700/1727	1840/1878	2039/2075	2170/2222	2132/2202	2363/2432
Diameter D	mm	ø 550	ø 650	ø 790	ø 790	ø 1000	ø 1200	ø 1250
Bedrijfsdruk	bar	6	6	6	6	6	6	6
Gewicht (zonder isolatie)	kg	56	75	102	120	201	251	292
Model		3000	4000	5000	6000	7000	8000	9000
Inhoud	L	3000	4000	5000	6000	7000	8000	9000
Hoogte H / Montagehoogte Hm	mm	2715/2775	2745/2815	2870/2960	3370/3447	3101/3185	3545/3620	3290/3405
Diameter D	mm	ø 1250	ø 1400	ø 1600	ø 1600	ø 1800	ø 1800	ø 2000
Bedrijfsdruk	bar	6	6	6	6	6	6	6
Gewicht (zonder isolatie)	kg	330	470	574	652	750	830	900

10 bar

Model		300	500	800	1000	1500	2000	2500
Inhoud	L	300	500	800	1000	1500	2000	2500
Hoogte H / Montagehoogte Hm	mm	1410/1432	1700/1727	1840/1878	2039/2075	2170/2222	2132/2202	2363/2432
Diameter D	mm	ø 550	ø 650	ø 790	ø 790	ø 1000	ø 1200	ø 1250
Bedrijfsdruk	bar	10	10	10	10	10	10	10
Gewicht (zonder isolatie)	kg	56	75	102	120	201	251	292

Model		3000	4000	5000	6000	7000	8000	9000
Inhoud	L	3000	4000	5000	6000	7000	8000	9000
Hoogte H / Montagehoogte Hm	mm	2715/2775	2745/2815	2870/2960	3370/3447	3101/3185	3545/3620	3290/3405
Diameter D	mm	ø 1250	ø 1400	ø 1600	ø 1600	ø 1800	ø 1800	ø 2000
Bedrijfsdruk	bar	10	10	10	10	10	10	10
Gewicht (zonder isolatie)	kg	330	470	574	652	750	830	900

Verwijderbare zachte PU thermische isolatie van 100 mm dik met PVC buitenbekleding in RAL 9006

Model		300	500	800	1000	1500	2000	2500
Gewicht isolatie	kg	7,65	9,9	13,05	14,4	18,3	21,75	26,85
Model		3000	4000	5000	6000	7000	8000	9000
Gewicht isolatie	kg	30,3	38,85	47,4	55,95	64,5	73,05	81,6